



Fig. 1




09738855-121800


Fig.2




polyacrylic acid




polyvinyl acetal




polyvinyl pyrrolidone




polyethyleneimine




polyethylene oxide




styrene-maleic acid copolymer



polyvinylamine resin




polyallylamine




oxazoline group-containing
water-soluble resin

09738855-121800


Fig.3




ureaderivatives




alkoxymethylurea




N-alkoxyethyleneurea




ethyleneurea




ethyleneureacarboxylic acid




melamine derivatives



alkoxymethylmelamine derivatives




benzoguanamine



glycoluril


008721 5588E/60

Fig.4




0973855.121800

Fig.5




09738855-121800

Fig.6




09/38855-121800

Fig.7



00846 " 5585 121300

Fig.8
 PRIOR ART



09738855-121800

Table 1

Condition	Diameter of Via-Hole
Non Heat Treatment	150 μ m
120°C/60min	130 μ m
130°C/30min	100 μ m
140°C/30min	70 μ m

Table 2

Condition	Diameter of Via-Hole
Non Heat Treatment	150 μ m
110°C/10min	120 μ m
110°C/20min	100 μ m
110°C/30min	80 μ m
135°C/40min	40 μ m

Table 3

Condition	Diameter of Via-Hole
Non Heat Treatment	150 μ m
110°C/15min	120 μ m
120°C/15min	100 μ m
130°C/15min	80 μ m
135°C/20min	45 μ m

Table 4

Condition	Diameter of Via-Hole
Non Heat Treatment	100 μ m
120°C/30min	96 μ m
130°C/30min	90 μ m
140°C/30min	83 μ m

Table 5

Sample	Dielectric Constant 〔 1kHz 〕 〔 25°C 〕	Thermal Expansion 〔 Vertical 〕 〔 80~120°C 〕	Peel Strength 〔 90° Peel 〕 〔 25°C 〕
Evaluation Board A	4. 5	40ppm	980kg/cm
Evaluation Board B	4. 8	55ppm	970kg/cm

008721 5588E/60